
Technical specification

Max size	52 x 70 cm
Min size	12 x 18 cm
Productivitate	15.000 / A4
Lungime maxima falt	55 cm
Lungime minima falt	6 cm
Gramaj hartie	60 - 180 g/m ²
Alimentare Electrica	220V, 50 Hz

CONSUMURI

Compressor	3,6 kW
Alimentator pila inalta	0,25 kW
Primul falt	0,5 kW
Al doilea falt	0,5 kW
al treilea falt	0,5 kW
Unitatea de livrare	0,25 kW
Total	5,60 kW



heat separation system



vacuum drum and electronic pile height sensor



Operator control panel

Model FK-52.4.2.2 (4 plates + 2 + 2)


- Alimentare din pila de 60cm cu alimentator prin succiune si sensor de prezenta foaie.
- Tambur de alimentare cu vacuum
- Sistem sepapre coli
- Sistem electronic de variatie viteza
- Contor programabil
- Detector de coala dubla.



El
ektromechanical
double sheet detector



C
ombination fold rollers
and caliper gap set



M
anual sheet stop
adjustment with gauge

- 5 detectoare de defect faltuire.
- Pupitru de comanda si control a lungimii de faltuire. The storage capacity for 5 programmes.
- Autodiagnoza
- Verificator de coala cu memorie a imaginii ce detecteaza orice coala tiparita impropriu.
- Opreire manuala in caz de pericol.
- Auto compensator cu role
- Dispozitiv de rituire, perforare si despicare.
- Standuri mobile.
- Protectie antizgomot.

