

KH-200P flat hot stamping machine



Feature:

1. Crank design, strong pressure and low air consumption.
2. Stamping pressure, temperature and speed adjustable.
3. Manual worktable in/out for safety operation.
4. XYZ adjustable worktable.
5. Auto foil feeding and winding.
6. Height of stamping head adjustable.
7. Worktable shuttle with gear and rack for round product stamping.
8. It is widely used for electric, cosmetic, jewelry package, toy and surface decoration.

Options:

1. Auto sliding in/out worktable

2. 3-sided guarding for safety operation
3. Sensor system for image registration
4. Control panel: standard key-pressed panel or touch screen panel optional

Parameter:

Model	KH-200P	KP-300P
Max stamping area	200×250mm	300×400mm
Worktable Size	2050×300mm	350×450mm
Stamping Head Stroke	50mm	
Article Height	200mm	
Temperature	Room Temperature~280□	
Stamping Pressure	2000-3000kgf/cm ²	
Max. Stamping Speed	1100pcs/hr	1000pcs/hr
Air Pressure	6~7bar	
Air Consumption	≤250L/min	≤300L/min
Power Supply	220V 60Hz/50Hz	
Weight	180kg	240kg
Dimension	800x600x1750 mm	950x730x1850 mm